



# Boost Charger™

## Ultrafast EV Charging with Integrated Energy Storage

The FreeWire Boost Charger is an ultrafast DC charger for electric vehicles (EVs). The battery-integrated design enables Boost Charger to easily connect to existing electrical infrastructure without costly construction and complex permitting. Boost Charger has a 160 kWh battery capacity with 120 kW output and only 27 kW or less input, making it ready for current and next generation EVs.



### TURNKEY INSTALLATION

**Plug & Play:** battery-integrated design connects to the existing low-voltage grid, enabling cost efficient installation in hours

**Small Footprint:** space efficient design means no unsightly and expensive electrical infrastructure

**Lower Operating Costs:** energy buffering technology limits input from the grid, reducing costly demand charges

### PREMIUM CHARGING

**Ultrafast Charging:** charges EVs up to 100 miles in 10 minutes

**Dual Charging:** provides simultaneous charging that's universally compatible with all EV models

**Customizable Design:** option for custom branded unit including point-of-sale integration for retailers

### FUTURE-PROOF

**Smart & Connected:** integrated energy management software and OCPP communications compatible with any charging network

**Flexible Deployment:** easy to relocate depending on charging demand and site access limitations





**ENERGY STORAGE**

Energy Chemistry	Lithium-ion (NMC)
Energy Storage Capacity	160 kWh

**ELECTRICAL SPECIFICATIONS (OUTPUT)**

Supported Connector Types	CCS1 / CCS2 CHAdeMO
Charge Ports	2
Max Output Power (DC)	CCS: 120 kW CHAdeMO: 100 kW Combined: charge 2 vehicles simultaneously at up to 60 kW each
Max Output Current (DC)	CCS: 300 A CHAdeMO: 200 A

**ELECTRICAL SPECIFICATIONS (INPUT)**

Power (AC)	≤ 27 kW
Voltage (AC)	3-phase 208 V, or; Split-phase 240 V
Current	3-phase: 100 A service, 80 A typical, or; Split-phase: 150 A service, 120 A typical
Frequency	50 / 60 Hz ± 1%

**MECHANICAL SPECIFICATIONS**

Dimensions	101 cm (40") L x 109 cm (43") W x 243 cm (96") H
Cable Length from Station	381 cm (150")
Weight	1,720 kg (3,800 lbs)



**ENVIRONMENTAL SPECIFICATIONS**

Installation Location	Outdoor
Enclosure Protection Rating	IP 54
Operating & Storage Temperature	-20° C (-4° F) to +55° C (131° F)
System Round Trip Efficiency	> 90%*

*\*at ambient temperature*

**NETWORK & USER INTERACTION**

Network Connection	4G LTE, Ethernet
Communications	OCPP 1.6-J
User Interface Screen	61 cm (24") ruggedized LCD touchscreen
Credit Card Reader	Standard
Payment Methods Accepted	Credit cards, NFC, MIFARE, FeliCa
Access Control & Authentication	RFID: ISO 14443A/B, ISO 15693
Safety & Compliance	UL2202, UL2231-1, UL2231-2, UL991, UL1973 (battery pack) FCC part 15 Class A (U.S.)



**FreeWire Technologies, Inc.**

1933 Davis Street, Suite 301A  
San Leandro, CA 94577

**Contact Us**

Call: 415.779.5515

Email: [sales@freewiretech.com](mailto:sales@freewiretech.com)

Visit: [www.freewiretech.com](http://www.freewiretech.com)